VANDAELE



TVI20 WOOD CHIPPER

VANDAELE*

TV I 20 WOOD CHIPPER



Standard tractor driven 3-point machine



Diesel engine driven machine on road trailer

The smallest performer in the range. For chipping of twigs, branches & stems of any type of wood with maximum diameter of 120mm / 5". Available in tractor driven version and diesel engine version.

The TV 120 is unique in its kind because:

- SIMPLE MAINTENANCE
- NO SHARPENING OF THE KNIVES REQUIRED!
- MEETS ALL CE SAFETY REGULATIONS
- OPTIMUM SAFETY
- SAFETY BAR SURROUNDING THE INFEED FUNNEL (VANDAELE® patent n° 2003/0590)

Features and benefits of the Vandaele wood chippers:

- · Standard equipped with TUNGSTEN-CARBIDE knives and counter knives in sections.
- · Sections are easily replaceable
- · Renders sharpening and adjusting of the knives superfluous,
- · Extreme long life span,
- · Noise reduced knife disc, integrated in a wear resistant housing,
- · Direct power linkages, no belts or chain drives,
- · Robust construction, years of experience incorporated,
- · Very big capacity.

Standard machine colour: RAL 2011 (safety colour) Our renowned junior.





TV120 P; Can be powered by small tractors, as from 20 HP.



TV120 D; Powerful, largely specked diesel engine.

Technical specifications:

TV 120;

Basic machine:

- · Chipper disc ø 680 mm, equipped with 2 knives in carbide tungsten
- · Counter knife in carbide tungsten
- · 2 hydraulically driven infeed rolls with reverse coupling, chip size regulation from 1 till 25 mm,
- . Ejector chute 2,3 m high, 300° revolving (EN13525)
- . Wood diameter round wood max: 120 mm / 5"
- . Infeed opening between the infeed rolls: 200 mm x 120 mm / 7.5" x 5",
- · Noise reducing coating.

TV120 P; tractor driven:

Standard

- Infeed rolls powered by means of tractor hydraulics (2 hoses with quick couplers),
- . PTO driven: 1000 RPM (540 RPM optional)
- · Minimum required tractor power: 20 HP,
- · Designed for tractor 3-point linkage,
- · PTO shaft included.

Optional:

- · Infeed rolls powered by means of incorporated pump group,
- · 540 RPM gearbox,
- · Antistress-system
- suspended trailer with wheels 175/13, with fixed draw bar and support wheel, slow speed 40 km/h, mudguards and lights,
- · Free wheel PTO shaft,
- · Transparent flaps in the infeed funnel,
- · Light bar on top of the funnel, protected,
- . Different RAL colour instead of RAL 2011 of RAL 7011,
- · Hour meter.


TVI 20 D; diesel engine driven:


Standard

- Knife disc speed = 1250 RPM,
- Integrated LOMBARDINI diesel engine, air cooled, 2 cyl, 21 kW, 28.5 HP,
- Direct driven knife disc by means of a flexible coupling,
- · 12 Volt battery, power cut battery key,
- · Hour meter, low fuel warning light,
- · ANTISTRESS SYSTEM,
- Basic unit mounted on a high speed trailer, 80 km/h, with mudguards and lights, tires 185/14, fixed drawbar, ball coupling and support wheel.

Optional:

- Spare wheel 185/14,
- · Transparent flaps in the infeed funnel,
- . Different RAL colour instead of RAL 2011 of RAL 7011.





TV120 D; Trailer with over run brake system.



TV120 D; Air cooled LOMBARDINI diesel engine, 2 cylinder; 21 kW - 28.5 HP.



Anti-Stress system comes standard on diesel machines, optional on tractor driven units.



Exhaust chute 300° turn able (safety), transportation locking system included.





Transparent flaps in the funnel (optional).

"Shell" structure = robust infeed funnel in one piece, no foldable parts



Optimum operator safety system: safety bar wrapped around the entire infeed funnel (VANDAELE® patent)



The Vandaele® products have been developed and produced in accordance with the ISO 9001 : 2000 quality management system.